

# Delock 2.5 External Enclosure SATA HDD > Multiport USB 3.0 + eSATAp (up to 15 mm HDD)

## Description

This aluminium-enclosure by Delock enables you to install a 2.5 SATA HDD or SSD and provides up to 4 different connecting options due to its special Multiport USB 3.0 + eSATAp interface. The Multiport is a combination of eSATA and USB 3.0 interface, which supports a fast data transfer and a voltage supply of up to 5 V. For extra voltage supply, when connecting via eSATA, you will find an additional power cable included in delivery.

The enclosure is especially suitable for different hard disk with a height up to 15 mm.

### Connecting options:

1. USB 3.0 (Power via USB)
2. USB 2.0 (Power via USB)
3. eSATAp (Power Over eSATA combo-connection  
eSATA+USB - eSATA for data and USB for power)
4. eSATA (eSATA for data and power via included USB power cable)



## Specification

- External aluminium-enclosure for 2.5 SATA 1.5 Gb/s and 3 Gb/s HDD or SSD
- Supports different hard disk height: 9 mm, 12.5 mm 14.5 mm or 15 mm
- Connector
  - external: 1 x Multiport USB 3.0 + eSATAp
  - 1 x DC for power when connecting via eSATA
  - internal: SATA 22 pin (data + power)
- Dimension DC connector:
  - Length of pin: 9.5 mm
  - ø 3.5 / 1.3 mm
  - Polarity: ground outside, plus inside
- Data transfer rate:
  1. USB 3.0 up to 5 Gb/s
  2. USB 2.0 up to 480 Mb/s
  3. eSATA up to 3 Gb/s
- Enclosure with full-PCB
- LED indicator for power and access
- Dimension (LxWxH): 136 mm x 80 mm x 21 mm
- Hot Swap, Plug & Play

## Item No. 42492



EAN 4043619424924

Country of origin Taiwan, Republic Of  
China

**System requirements**

- Windows 2000/Server-2003/XP/Vista/7, Mac OS 10.5/10.6
- PC or notebook with
  1. a free USB 3.0 port
  2. or a free USB 2.0 port
  3. or a free eSATAp port
  4. or o free eSATA port and a free USB port for power

**Package content**

- 2.5 external enclosure
- USB 3.0-A/A cable (ca. 50 cm)
- DC-USB power cable (ca. 80 cm)
- eSATAp cable
- Cover, screwdriver, screws
- User manual

**Package**

- Retail Box

**Images**

